



FANS | LIGHTING | APPLIANCES



## About RR Global

RR Global, a USD 1.25 billion conglomerate has moulded its success on innovation. Since the foundation of the brand, its architects opted that innovation is the key to success of every product in the brand. It was a really courageous decision because at that point in time categories like wires and cables were highly commoditized. This optimistic development led to the creation of a brand - RR Kabel, a name which is admired worldwide with existence over 90+ countries across the globe.

Presently the company is ranked amongst the top three retail wire manufacturers across the nation. It is also the largest consumer of copper in India, an achievement which no one would have imagined a cable and wire company to be capable of and that is the reason they are preferred by clients who are some of the largest copper manufacturer in the country.

RR Global takes honour in establishing 9 companies and global offices, primarily in the U.A.E and Bangladesh. In their endeavour to set international benchmarks, RR Kabel has received 19 international accreditations. They are the first in India to have BASEC (U.K.), UL (U.S.A.), VDE (Germany), among others for its wide range of cables including ISO 50001 and ISO 14001.

Across the course of four decades, their impulse towards innovation to achieve success and hard work steered them to earn phenomenal recognition with RR Kabel becoming the desired choice for wires and cables not only in India but also on a global platform.

RR Global India focusses on cutting edge technology and research to enhance efficiency, reliability, and safe conduction of electricity. This in turn supported the core of the company's engineering endeavour which is to guarantee safe environments everywhere- offices, commercial spaces, industrial plants, and residences.



## **COMFORT** is in the AIR

RR Fans Product range is offered by RR Global, a USD 1.25 billion conglomerate in the electrical sector with a presence in over 85 countries globally.

Flagship brand RR Kabel (Wires & Cables) along with other Consumer Products Brand RR Fans, RR Lighting, RR Switches, RR Appliances and Arraystorm (Commercial Lighting) are part of marquee RR Global Brand.

RR Fans offer a wide range which is premium looking, high on performance and priced economically for various residential, commercial, institutional and industrial purposes. The range spectrum spreads across Ceiling Fans, Table / Wall / Pedestal Fans, Ventilation Fans, Exhaust Fans (Light Duty / Heavy Duty), Air circulators.











White



Ceiling Fan

- Energy efficient BLDC motor
- Run 3 times longer on Inverter
- Unique hoop-shaped trims for enhanced aesthetics
- Aerodynamically engineered blade profile for best-in-class performance

SWEEP	POWER	SPEED	AD
1200mm	35W	370 RPM	220m³/min



Anti-Dust Coating
Dust Retardant



RR

Remote Control



Sparkling Silver









RRAMOUT



**BLDC** fan

Anti-Dust Coating Dust Retardant



High Air Delivery



Remote Control

- Unique hoop-shaped trims for enhanced aesthetics
- Anti-dust coating for ease of maintenance
- High speed operation for better air experience
- High air delivery for elevated comfort level
- Aerodynamically engineered blade profile for best-in-class performance

SWEEP	POWER	SPEED	AD
1200mm	35W	360 RPM	220 m³/min







Pearl White







High Air

Thrust

Silent

**BLDC** motor



Energy Saving Ceiling Fan



- 26 watt BLDC fan with unique design developed in house.
- Built with best specification & is having highest service value of 8.27.
- LED speed indicator which also acts as night light.
- No drop in speed at low voltages.
- Smart remote with full speed mode and sleep timer.

SWEEP	POWER	SPEED	AD
1200mm	26W	350 RPM	215m³/min



Remote 6:

65% Energy Saving









- 27W Super Power Saver with BLDC Motor
- Very high service value 8.0 (Better energy efficiency and Air delivery)
- Total Harmonic Distortion (THD) ≤ 10% (With remote Mode operation only) ensures safe running on inverter

SWEEP	POWER	SPEED	AD
1200mm	27W	335 RPM	217m³/min







Smoke Brown



White

CEILING FAN

Deluxe



Energy Efficient BLDC Motor



RA

Remote Control



Low Power Consumption









- Silent Operation
- Total Harmonic Distortion (THD) ≤ 5%
- High Speed BLDC fan

SWEEP	POWER	SPEED	AD
1200mm	30W	380 RPM	220m³/min







Energy Efficient BLDC Motor



Remote Control



Low Power Consumption











- Superb paint finish to enrich the décor of your interior
- Modern and stylish design
- High air thrust

SWEEP	POWER	SPEED	AD
1200mm	50W	380 RPM	225m³/min





Aerodynamic Blades



High Speed @380 RPM

Disclaimer : Due to continuous product improvements, Product Image shown may vary from actual product.



Berkeley Gold



Cool blue Silver



Cedar Brown







- Larger motor body for quicker heat dissipation
- Simple clean design with a bit of ostentatiousness
- Single shade metallic finish for classy looks

SWEEP	POWER	SPEED	AD
1200mm	44W	370 RPM	220m³/min



Powerful motor



Aerodynamic Blades



Rose Gold







Ale Brown

- Larger motor body for quicker heat dissipation
- Simple clean design with a bit of ostentatiousness
- Single shade metallic finish for classy looks

SWEEP	POWER	SPEED	AD
1200mm	56W	350 RPM	230m³/min





Aerodynamic Blades



RR

Decorative Trims



High Air Delivery



Champagne Gold



Aqua Silver







- Unique hoop-shaped trims for enhanced aesthetics
- · Anti-dust coating for ease of maintenance
- High speed operation for better air experience
- High air delivery for elevated comfort level
- Aerodynamically engineered blade profile for best-in-class performance

SWEEP	POWER	SPEED	AD
1200mm	55W	380 RPM	220m³/min





Anti-Dust Coating
Dust Retardant



High Air Delivery



Sparkling Silver



Charcoal Black







- Exotic rich looks with metallic paint finish.
- Modern styling with decorative ring and trims gives a look of elegance.
- Superior air delivery performance: 225m³/min
- Powerful motor to ensure longer life.

SWEEP	POWER	SPEED	AD
1200mm	50W	350 RPM	225m³/min







Steel Grev



Marine Blue



Caramel Gold



motor







Decorative Trims







Ceiling Fan
VINDR<sup>+</sup>

- High speed decorative fan
- Anti dust metallic paint finish
- Wide and long aluminium blades for wider air circulation.

SWEEP	POWER	SPEED	AD
1200mm	55W	370RPM	220m³/min



Anti-Dust Coating



High Air Thrust



High Speed @370 RPM



Decorative Trims



Pearl Brown

Also available in Rose Gold color







Honey Gold



RR

- Aerodynamically designed blades for better air thrust
- Elegant motor ring and unique blade trims

SWEEP	POWER	SPEED	AD
1200mm	44W	370RPM	220m³/min





Powerful motor



Double ball bearings



High Air Thrust



High Speed @370 RPM



Mint White











- Strong motor to operate even at low voltage conditions.
- Anti dust metallic paint finish
- Wide and long aluminium blades for wider air circulation.
- Sleek and light weight aluminium body.
- High speed operation.

SWEEP	POWER	SPEED	AD
1200mm	55W	370RPM	220m³/min



Powerful motor



Anti-Dust Coating



High Air Thrust



High Speed @370 RPM



Caramel Gold



Pearl White







RR

 Unique oval shaped blade design for better aerodynamics

- Powerful motor to produce high speed of rotation
- Bigger motor for better heat dissipation

SWEEP	POWER	SPEED	AD
1200mm	54W	380RPM	220m³/min







Double bal bearings



High Air Thrust



High Speed @380 RPM





Pearl White

RR

Ceiling Fan
VAYOO SUPER

- Dust retardant blades for lesser dust accumulation.
- High Speed for Breeze effect.
- Aerodynamically balanced blade for high efficiency and low noise.

SWEEP POWER SPEED AD
1200mm 52W 400 RPM 215m³/min







Aerodynamically balanced blade



High Air Thrust



High Speed @400 RPM



Pearl Brown



Caramel Gold



Disclaimer: Due to continuous product improvements, Product Image shown may vary from actual product.





Sub-Economy Range





RR

- Precisely balanced aerodynamically designed blades
- Suitable for low voltage operation
- Aluminium die cast motor & blades

SWEEP	POWER	SPEED	AD
600mm	70W	745 RPM	140m³/min
900mm	47W	450 RPM	150m³/min
900mm(SF)	50W	600 RPM	155m³/min
1200mm	52W	400 RPM	215m³/min
1400mm*	58W	290 RPM	245m³/min

Vayoo SF Available in 900 mm sweep with 600 RPM.



Low Voltage Operation



Powerful motor



Noiseless operation



High Speed



Brown



MORE STARS MORE SAVINGS POWER SAVING





- Precisely balanced aerodynamically designed aluminium blades.
- Double ball bearings for smooth operation.
- Strong 14 pole motor for silent operation & longer life.
- Service value above 4.2

SWEEP	POWER	SPEED	AD
1200 mm	50W	350 RPM	210m³/min



Powerful motor



Double ball bearings



Aerodynamic Blades











- Decorative ceiling fan
- Aluminium pressure die cast motor body
- Strong motor with high air delivery
- Double ball bearings for smooth operation
- Powder coated surface finish for better scratch resistance.
- High speed operation.

SWEEP	POWER	SPEED	AD
900 mm	₩ 48W	450 RPM	150m³/min
1200 mm	52W	400 RPM	210m³/min
1400 mm	🤛 58W	300 RPM	245m³/min



bearings



motor



Decorative Trims



High Speed @400 RPM



Brown



White



Smoke Brown



Disclaimer: Due to continuous product improvements, Product Image shown may vary from actual product





- Aluminium pressure die cast motor body
- Strong motor with high air delivery
- Double ball bearings for smooth operation
- Powder coated surface finish for better scratch resistance

SWEEP	POWER	SPEED	AD
600 mm	80W	850 RPM	110 m³/min
900 mm	47W	450 RPM	150 m³/min
1200 mm	50W	400 RPM	210 m³/min
1400 mm	58W	300 RPM	245 m³/min





Double ball bearings



Powerful motor



High Air Thrust



High Speed



Ivory



Brown









High Air

Thrust

Double ball

bearings

Low Voltage

Operation

HIGH SPEED

High Speed

@400 RPM

AD



Ceiling Fan

DROOT

Eco

• Elegant Design

- High Lift Angle of Blade for wider Air Spread
- Operational at Low Voltage as well
- Double Shielded Ball Bearing in Motor for Long Life

SWEEPPOWERSPEEDAD1200 mm52W370 RPM210m³/min



Low Voltage Operation



Brown

Double ball bearings



High Air Thrust



Ivory




White



Smoke Brown













## Pedestal & Wall Fan P\$RTO HS



- Smooth oscillation
- Elegant design
- Premium ABS Blades
- High air delivery

SWEEP	POWER	SPEED	AD
400 mm	120W	2300 RPM	100m³/min

COLOUR:

Blue

White

Burgundy



High speed



Hi Air Throw



Thermal overload protection



Aerodynamic Blade









- 5 Blades for Soothing Air Delivery
- Strong Motor
- Smooth Oscillation

SWEEP	POWER	SPEED	AD
400 mm	58W	1350 RPM	70m³/min



COLOUR: Blue & White





Black & Yellow



High Air Delivery



Low Noise



protection



Strong Motor



## Multipurpose Fan **B**reezemate



- Multipurpose fan
- 360° Rotation
- High air delivery/ Air thrust



SWEEP	POWER	SPEED	AD
230 mm	45W	2400 RPM	30m³/min
300 mm	70W	2200 RPM	50m³/min





Operation



Motor





Wall/ Table Fan





- Powerful motor with high grade copper
- Smooth oscillation for better coverage
- Rust-proof body and blades
- Elegant design
- High speed operation for high air thrust
- High air delivery

SWEEP	POWER	SPEED	AD
400 mm	115W	2150 RPM	90m³/min
300 <sup>°</sup> mm	100W	2200 RPM	70m³/min

\*Applicable to Wall fan only

COLOUR: Ash grey





White





High



Full copper motor



Thermal overload



High air

speed

protection (TOP)

delivery





### **TPW Fan CALID**

- Powerful motor with high grade copper
- Smooth oscillation for better coverage
- Rust-proof body and blades
- · Elegant design
- Silent operation
- · High air delivery
- Thermal overload protection\*

SWEEP	POWER	SPEED	AD
400mm	58W	1330 RPM	70m³/min

\*Applicable to Wall fan only

COLOUR: Blue









Full copper motor

90°

Silent operation oscillation even on inverter air delivery

High






# GETT®

- Heavy duty motor
- High air thrust
- Heavy base for better stability
- Telescopic height adjustment (700-1000 mm)

SWEEP	POWER	SPEED	AD
400 mm	50W	1330 RPM	70m³/min

COLOUR: Aqua Marine 
Sulphur Black







Jerk-free oscillation



Silent
Operation even
on inverter



Adjustable Height<sup>#</sup>

40





## TPW Fan

- Elegant design to elevate your room decor
- Powder coated guard and polymer ring to protect against corrosion
- Tilt adjustment for adjusting the fan at desired angle
- In-built thermal overload protection for enhanced safety
- Oscillation function for better coverage

SWEEP	POWER	SPEED	AD
400 mm	60W	1350 RPM	70m³/min

COLOUR: White



High air delivery



Aerodynamically designed blades



3 speed switch control



Adjustable height#



Full copper Motor



Thermal overload protection (TOP)





## **HAILST&RM**



- Strong Motor
- Smooth Oscillation
- Premium ABS Blade
- 3 speed switch control

SWEEP	POWER	SPEED	AD	
400 mm	110W	2200 RPM	120m³/min	

COLOUR: Black



High air delivery



High speed



Strong Motor



Thermal Protection

#### **FARRATA**

#### **FARRATA LX**





- Heavy Duty Motor
- Thermal Overload Protection for Enhanced Safety
- High Air Thrust with minimal noise
- Telescopic height adjustment
- 3 speed rotary switch control

SWEEP	POWER	SPEED
500mm	150W	1400 RPM



- Heavy duty motor
- · High air thrust
- Heavy base for better stability
- Telescopic height adjustment (700-1000 mm)
- 3 speed rotary switch control

SWEEP POWER		SPEED	
500mm	150W	1400 RPM	



Full copper motor



High air delivery



Thermal Overload Protection (TOP)

Also Available "Oscillating Farrata Fan"



Full copper motor



Adjustable height







- High air thrust for instant relief
- Heavy base for better stability
- Heavy duty motor

		SPEED	AD
450 mm	100W	2400 RPM	110 m³/mir



High Speed Full copper @2400 rpm motor



High Air Thrust



# Ventilation Fans



#### **OXYBREEZ**





- PP blades designed for powerful suction
- Auto dust protection louvres to protect from foreign objects like birds
- Suitable for washrooms/bathrooms

SWEEP	POWER	SPEED	AD	DUCT SIZE
6 in	25 W	1400 RPM	270 m³/hr	174x174mm
8 in	30 W	1300 RPM	480 m³/hr	240x240mm
10 in	35 W	1300 RPM	750 m³/hr	290x290mm



Auto dust protection louvres



Powerful Air Suction



Easy Clean

#### **OXYBREEZ LX**





- PP blades designed for powerful suction
- Auto dust protection louvres to protect from foreign objects like birds
- Suitable for washrooms/bathrooms

SWEEP	POWER	SPEED	AD	DUCT SIZE
6 in	30 W	1400 RPM	265 m³/hr	190x190mm
8 in	32 W	1300 RPM	570 m³/hr	240x240mm
10 in	35 W	1300 RPM	750 m³/hr	290x290mm



Auto dust protection louvres



Powerful Air Suction



Easy Clean





- Innovative modern design suitable for best interiors
- Bird screen for protection against birds and foreign matter
- Easy to mount; can be mounted on glass panel

SWEEP	POWER	SPEED	AD	DUCT SIZE
4 in	15 W	2400 RPM	140 m³/hr	109 Ø mm
6 in	20 W	2000 RPM	275 m³/hr	150 Ø mm
8 in	42W	1800 RPM	570 m³/hr	200 Ø mm



Silent Performance



Easy Clean



Powerful Air Suction

#### **OXYFLO SS**





- High Quality motor for effective weather control
- Rust proof body for durability
- Easy to mount; can be mounted on glass panel

SWEEP	POWER	SPEED	AD	DUCT SIZE
4 in	15 W	2400 RPM	140 m³/hr	98x98mm
6 in	20 W	2000 RPM	275 m³/hr	145x145mm



Silent Performance



Powerful Air Suction



Easy Clean

#### **OXYBREEZ SQR**





- Bird screen for protection against bird and foreign matters
- Ideal for kitchen / bathroom

SWEEP	POWER	SPEED	AD	DUCT SIZE
6 in	34 W	2300 RPM	570 m³/hr	190x185mm
8 in	38W	1800 RPM	823 m³/hr	243x238mm



Silent Performance



Easy Clean



Powerful Air Suction

#### **OXYBREEZ LDBX / LDBX HS**



- Suitable for store room, kitchen and bathroom
- Front guard for protection against birds and foreign matter
- Metal blade with powder coated finish for longer life

SWEEP	POWER	SPEED	AD	DUCT SIZE
9 in	45 W	1370 RPM	600 m³/hr	233x 233mm
12 in	65 W		,	317x317mm
6 in (HS)	50 W	2400 RPM	500 m³/hr	242x 242mm
9 in (HS)	70 W	2400 RPM	800 m³/hr	233x 233mm
12 in (HS)	90 W	2200 RPM	1600 m³/hr	317x317mm







Powerful Air Suction



Guard

#### **OXYBREEZ LDEX**



- Suitable for kitchen
- Front guard for protection against birds and foreign matter
- Metal blade with powder coated finish for longer life
- Rubberized foundation for reduced vibrations

SWEEP	POWER	SPEED	AD
9 in	45 W	1400 RPM	750 m³/hr
12 in	70 W	1400 RPM	1600 m³/hr



Powerful Copper Motor



Powerful Air Suction



# Industrial Fans

#### **HEAVY DUTY EXHAUST FAN**



- Aerodynamically designed metal blades for higher air delivery
- Anti-corrosive treatment and attractive metallic finish
- 4 blade with double ball bearing motor

SWEEP	POWER	SPEED	AD
300*mm	100 W	1400 RPM	2000 m <sup>3</sup> /hr
380 mm	150 W	1400 RPM	4000 m <sup>3</sup> /hr
450 mm	375 W	1400 RPM	6200 m³/hr
600 mm	480 W	900 RPM	10400 m <sup>3</sup> /hr

\*Available in Single Phase only

Available in Single and Three Phase







Powerful Air Suction



Note: Warranty for 450mm HDEX DLX is 2 years

#### **AIR CIRCULATOR**





Wall Mounted Fan

- Heavier base to ensure absolute stability
- 90° oscillation for wider coverage
- Completely enclosed heavy duty energy efficient motor with double ball bearing for longer life.

**SWEEP POWER** SPEED AD 10000 m<sup>3</sup>/hr 450mm 100 W 1400 RPM 600mm 200W 1400 RPM 16000 m<sup>3</sup>/hr 23000 m<sup>3</sup>/hr 750mm 300 W 1400 RPM

Available in Single Phase and Three Phase only



Pedestal Fan

Heavy Duty Copper Motor



High air delivery





"We bring to you an exceptional and extensive range of LED Lighting products to suit every requirement across Residential, Commercial, Institutional & Industrial sectors. The range spectrum spreads across Bulbs, Battens, Panels, Down-lighters, Floodlights, Streetlights, High-Bays. Each one is perfectly crafted to help you beautifully illuminate your home, office, or outdoor space."





### RRLIGHTING

#### 9W | 12W | 15W



#### **APPLICATION**



Hotels



Residential







Malls

- Overcharging and deep discharge protection
- Inbuilt charging circuit for battery
- Charging Time: 10 hrs (Full Charge)
- Emergency backup time up to 3.5 to 4Hrs max.
- Battery type Li-on, 3.7V, 2200 mAh









High Power backup

Ecofriendly

Uniform Light Distribution

Long Battery Life

Input Power	Size(mm) ØxH	Beam Angle	PF	Lumen
9W	70x140	120°	>0.95	900
12W	70x140	120°	>0.95	1150
15W	80x160	120°	>0.95	1500

\* Lumen may vary as per colour.



#### **LED HIGH BEAM BULB - AVIDITE Plus**

#### 3W | 5W | 8W | 10W | 12W | 15W | 19W | 23W



- High brightness
- Wide operating voltage
- No glare
- Non-dimmable

#### **LED HIGH BEAM 2 STAR BULB - AVIDITE Plus**

Input Power	Size(mm) ØxH	Beam Angle	PF	Lumen
3W	50x92	210°	>0.9	315
5W	60x111	210°	>0.9	525
8W	60x111	210°	>0.9	840
10W	60x111	210°	>0.9	1000
12W	65x120	210°	>0.9	1260
15W	65x133	210°	>0.9	1575
19W	80x151	210°	>0.9	1995
23W	80x151	210°	>0.9	2415

<sup>\*</sup> Lumen may vary as per colour.

#### LED HIGH BEAM 2 STAR BULB - AVIDITE DLX

Input	Size(mm)	Beam	PF	Lumen
Power	ØxH	Angle		
9W	60x111	210°	>0.9	945

#### **APPLICATION**









Hotels

Residential

Offices

Malls



#### **LED NIGHT LAMP - AVIDITE**

#### 0.5 W



- Ultra bright SMD LED
- High lumen efficacy
- High stability, long life span
- Plug in type fitment

Input Power	Size(mm) ØxH	Beam Angle	Colour	Base
			White	
			Red	
0.5W	45x70	270°	Yellow	B-22
			Blue	
			Green	

#### MULTICOLOUR BULB - AVIDITE

#### 0.5 W



- Ultra bright SMD LED
- High lumen efficacy
- High stability, long life span
- Plug in type fitment

Input Power	Size(mm) ØxH	Beam Angle	Colour	Base
			CDL, NW	
			WW	
0.5W	45×70	270°	Red	B-22
			Green	
			Blue, Pink	





#### 0.5 W



- Ultra bright SMD LED
- High lumen efficacy
- High stability, long life span

Input Power	Size(mm) ØxH	Beam Angle	Colour
			White
			Red
0.5W	45x75	270°	Yellow
			Blue
			Green
			Pink
			Orange







#### LED INTEGRATED TUBE LIGHT - SWANK / SWANK Classic

#### 5W | 9W | 20W | 22W | 24W



- Efficient optical system for good quality lighting
- High brightness

- No uv/ir
- Eco friendly-mercury free
- Wide operating voltage

Instant start

• Easy installation (clamp based)

Non dimmable

• IP20

• Elegant design

No glare

#### **APPLICATION**



Hotels





Offices





Malls

Product	Input	Size	Beam	PF	Lumen	Type	ССТ
Name	Power	(mm)	Angle		@6500K		
Swank	5W	300	120°	0.9	500	Plastic	3000 - 6500K
Swank	9W	600	120°	0.9	900	Plastic	3000 - 6500K
Swank	20W	1135	120°	0.9	2000	Plastic	3000 - 6500K
Swank	22W	1135	120°	0.9	2200	Plastic	3000 - 6500K
Swank	24W	1135	120°	0.9	2400	Plastic	3000 - 6500K
Swank Classic	20W	1100	120°	0.9	2000	Plastic	3000 - 6500K

<sup>\*</sup> Lumen may vary as per colour.



#### **ALUMINUM LED BATTEN LIGHT - SWANK**

#### 36W



- High brightness
- Wide operating voltage
- No glare
- IP20

- Eco-friendly
- Instant start
- Non dimmable
- Easy installation (clamp based)

Input	Size	Beam	PF	Lumen	Туре	CCT
Power	(mm)	Angle		@6500K <sup>*</sup>		
36W	1185	120°	≥0.9	3600	Aluminium	3000
						6500K

<sup>\*</sup> Lumen may vary as per colour.

#### **LED Batten Light - SWANK 30W**



- High brightness
- Eco-friendly
- Wide operating voltage
- Instant start

• No glare

Non dimmable

• IP20

 Easy installation (clamp based)

Input Power		Beam Angle	PF	Lumen @6500K	Type	ССТ
30W	1185	120°	≥0.9	3000	Plastic	3000
						6500K

<sup>\*</sup> Lumen may vary as per colour.

#### **APPLICATION**











Malls

#### **APPLICATION**









Hotels Residential

Offices

Malls

Hotels

Residential

Offices





20W



- High brightness
- Wide operating voltage
- No glare
- IP20

- Eco-friendly
- Instant start
- Non dimmable
- Easy installation (clamp based)

Input Power	Size (mm)		PF	Lumen	Type	Colour
20W	1100	120°	≥0.9	NA	Plastic	Red, Blue Green, Pink

#### **APPLICATION**









Hotels

Residential

Offices

Malls





#### **RECESSED LED DOWNLIGHT - DEVIANT**

#### 3W | 5W | 7W | 10W | 12W



**APPLICATION** 







Hotels

Residential

Offices

Malls

• No Glare • No UV/IR • Eco-friendly • Wide Beam Angle

Product Name	Input Power	Operating Voltage Range	Power Factor	CRI	Lumen (Im)	Size- ØxH (mm)	Cut out Dia (mm)	Beam Angle
Deviant J	3W	100-300V AC -50Hz	>0.9	>80	210 lm <sup>*</sup> @6500K	78x31	Ø42	120°
Deviant S	5W	100-300V AC -50Hz	>0.9	>80	425 lm <sup>*</sup> @6500K	110×56	Ø72	120°
Deviant S	7W	100-300V AC -50Hz	>0.9	>80	595 lm <sup>*</sup> @6500K	110x56	Ø72	120°
Deviant Sleek	5W	100-300V AC -50Hz	>0.9	>80	425 lm <sup>*</sup> @6500K	111x33	Ø73	120°
Deviant Sleek	7W	100-300V AC -50Hz	>0.9	>80	595 lm <sup>*</sup> @6500K	111×33	Ø73	120°

Deviant S (AL Body)	10W	100-300V AC -50Hz	>0.9	>80	850 lm <sup>*</sup> @6500K	110×47	Ø70	120°
Deviant S (AL Body)	12W	100-300V AC -50Hz	>0.9	>80	1020 lm <sup>2</sup> @6500K	110×47	Ø70	120°

<sup>•</sup> Color Available: Red, Green, Blue, Pink, WW, NW, CDL.

<sup>\*</sup> Lumen may vary as per colour.



#### RECESSED JUNCTION BOX LED DOWNLIGHT - DEVIANT J

#### 6W | 8W | 12W | 15W



- Fits perfectly in junction box & False low ceiling
- · Easy installation
- · Instant flicker free start
- Ideal for living room, bedroom, Hallway, small shops, kitchen, garage



High CRI



Only for Indoor



Anti-Glare Diffuser



Non-Dimmable

Input Power	Operating Voltage Range	Lumen (Im)	COD (Ø) (mm)	Size-ØxH (mm) (with spring)	CRI	Beam Angle	PF	THD
6W	100 <sub>~</sub> 300V AC- 50Hz	600 lm <sup>*</sup> @6500K	46	90 x 66.5	80	120°	0.90	25%
8W	100 <sub>~</sub> 300V AC- 50Hz	800 lm <sup>*</sup> @6500K	46	90 x 66.5	80	120°	0.90	25%
12W	100 <sub>~</sub> 300V AC- 50Hz	1200 lm <sup>*</sup> @6500K	46	140 x 68	80	120°	0.90	25%
15W	100 <sub>~</sub> 300V AC- 50Hz	1500 lm <sup>*</sup> @6500K	46	140 x 68	80	120°	0.90	25%





Hotels

Residential



Offices



Malls

- · Color Available 8W, 12W, 15W: WW, NW, CDL.
- · Color Available 6W: Red, Green, Blue, Pink, WW, NW, CDL.

<sup>\*</sup> Lumen may vary as per colour.



#### SURFACE CABINET LED DOWNLIGHT - MINTO

3W



- Ultra slim and sleek profile
- Uniform light throw, thus no dark spot
- Easy and secure installation with front Mount screws (caps provided)
- Ideal for cabinets, modular kitchens & showcases

Input	Operating	Working	Lumen	Size-ØxH	Beam
Power	Voltage Range	Temperature	(Im)	(mm)	Angle
3W	150-300V AC -50Hz	150-300V AC -50Hz	200 lm <sup>*</sup> @6500K	60x16.6	120°

<sup>·</sup> Color Available: Red, Green, Blue, Pink, WW, NW, CDL.

#### **APPLICATION**









Hotels

Residential

Offices

Malls

<sup>\*</sup> Lumen may vary as per colour.





#### 3W | 6W | 9W | 12W



APPLICATION



Wardrobes



Shelf Lighting



Furniture lighting



Hotels



Malls



Modern Gym

Long Life 25,000 hrs\*

• Sharp Beam Angle

Adjustable

Input Power	Operating Voltage Range	Lumen (Im)	COD (mm)	Size- ØxH (mm)	Material	Beam Angle
3W	100 <sub>~</sub> 300V AC- 50Hz	240lm* @6500K 225lm* @4000K 210lm* @3000K	54	75x44	PC	120°
6W	100 <sub>~</sub> 300V AC- 50Hz	510 lm*(@4000K   67   5		95x48	PC	120°
9W	100 <sub>~</sub> 300V AC- 50Hz	810lm* @6500K 765lm* @4000K 720lm* @3000K	88	117×52	PC	120°
12W	100 <sub>~</sub> 300V AC- 50Hz	1080lm* @6500K 1020lm* @4000K 960lm* @3000K	112	140x55	PC	120°

\* Lumen may vary as per colour.

# At 25°C (32°C)

<sup>·</sup> Color Available: WW, NW, CDL.





2W



- High brightness
- Non dimmable
- Instant start

• Long life upto 50,000hrs

Input Power	Operating Voltage Range	Lumen (Im)	COD (Ø) (mm)	Size- ØxH (mm)	Material	Beam Angle
2W	100 <sub>~</sub> 300V AC- 50Hz	140 lm <sup>*</sup>	33	39x16	PC	60°

<sup>•</sup> Color Available: Red, Green, Blue, WW, NW, CDL.



Wardrobes



Shelf Lighting



Furniture lighting



Hotels



Malls



Modern Gym

<sup>\*</sup> Lumen may vary as per colour.





# LED INTEGRATED PLASTIC PANEL - SPRUZZO

# 5W | 8W | 12W | 15W | 20W



### **APPLICATION**









Hotels Residential

Offices

Malls

- Durable thermally conductive plastic housing.
- Eye protection provided by acrlayic diffuser.
- Protection against open circuit voltage, short circuit voltage.
- Wide beam angle, no flickering, soft light design to protect your eyes.
- Inbuilt LED driver.
- Space saving design.
- High lumen efficacy.
- 3.0 KV surge protected.

CCT	Lumen*	Size-LxH	000		
		SIZE-LXH	COD	PF	CRI
	(lm)	(mm)	(mm)		
3000-6500K	350	82x36	60	>0.9	> 80
3000-6500K	640	116x36	96	>0.9	> 80
3000-6500K	1200	166x36	145	>0.9	> 80
3000-6500K	1500	166x36	145	>0.9	> 80
3000-6500K	1900	220x36	201	>0.9	> 80
4	8000-6500K 8000-6500K 8000-6500K	(Im) 3000-6500K 350 3000-6500K 640 3000-6500K 1200 3000-6500K 1500	(Im) (mm) 3000-6500K 350 82x36 3000-6500K 640 116x36 3000-6500K 1200 166x36 3000-6500K 1500 166x36	(Im)         (mm)         (mm)           3000-6500K         350         82x36         60           3000-6500K         640         116x36         96           3000-6500K         1200         166x36         145           3000-6500K         1500         166x36         145	(Im)         (mm)         (mm)           3000-6500K         350         82x36         60         >0.9           3000-6500K         640         116x36         96         >0.9           3000-6500K         1200         166x36         145         >0.9           3000-6500K         1500         166x36         145         >0.9


# To convert to surface panel, Ring also available for 8W, 12W, 15W and 20W Spruzzo Panel

<sup>\*</sup> Lumen may vary as per colour.





### 6W | 12W | 15W | 18W | 24W



- Unique zero bezel design for premiumness.
- 2835 type chip for high brightness, low decay, flicker free uniform and bright light.
- Environment friendly: no IR and UV radiation, no mercury and hazardous substance.
- Frosty diffuser for effecting angle of refraction for better illumination.

Input Power	Operating Voltage Range	Lumen (Im)	Size-ØxH (mm)	Beam Angle
6W	100-300V AC -50Hz	480 lm*@6500K	90 x 25	120°
12W	100-300V AC -50Hz	960 lm <sup>*</sup> @6500K	120 x 25	120°
15W	100-300V AC -50Hz	1200 lm <sup>*</sup> @6500K	156 x 25	120°
18W	100-300V AC -50Hz	1440 lm <sup>*</sup> @6500K	156 x 25	120°
24W	100-300V AC -50Hz	1920 lm <sup>*</sup> @6500K	190 x 25	120°

<sup>·</sup> Color Available: WW, NW, CDL.









Hotels Residential

Offices

Malls

<sup>\*</sup> Lumen may vary as per colour.





# 6W | 12W | 15W | 18W



- · Durable thermally conductive plastic housing.
- Inbuilt led driver.
- Eye protection provided by acrlayic diffuser.
- Space saving design.
- Ultra slim construction.
- 3.0 KV surge protected.
- Protection against open circuit voltage, short circuit voltage.
- Wide beam angle, no flickering, soft light design to protect your eyes.

Input Power	Size(mm) LXWxH	COD	PF	ССТ	CRI	Lumen* @6500K
6W	120x120x27	104	>0.9	3000 - 6500K	>80	390
12W	174×174×27	154	>0.9	3000 - 6500K	>80	840
15W	225x225x27	205	>0.9	3000 - 6500K	>80	1050
18W	225x225x27	205	>0.9	3000 - 6500K	>80	1260

<sup>· 6</sup>W Color Available: Red, Green, Blue, Pink









Hotels Residential

Offices

Malls

<sup>\*</sup> Lumen may vary as per colour.



# RR

### 3W | 6W | 9W | 12W | 15W | 18W



- Pressure die cast aluminium alloy housing for effective thermal management.
- More than 90% power factor HPF, 80% energy saving with low power consumption.
- · Wide beam angle, no flickering.
- Environmentally friendly, no interference, no hazardous substances.
- Eye protection provided by acrlayic diffuser.
- Ultra slim construction.
- Protection against open circuit voltage, short circuit voltage.
- Space saving design.
- 3.0 KV surge protected.

Input Power	Size(mm) LXWxH	COD	Beam Angle	PF	ССТ	CRI	Lumen @6500K
3W	85x85x20	70	104	>0.9	3000-6500K	>80	170
6W	120x120x25	105	154	>0.9	3000-6500K	>80	430
9W	120x120x25	105	205	>0.9	3000-6500K	>80	650
12W	170x170x25	155	205	>0.9	3000-6500K	>80	860
15W	170x170x25	155	205	>0.9	3000-6500K	>80	1080
18W	225x225x25	200	205	>0.9	3000-6500K	>80	1300

# **APPLICATION**



Hotels



Residential





Offices

Malls





## 36W



- Low power consumption
- No glare soothing to eye
- Excellent colour rendering
- No harmful UV & IR radiation
- · Aesthetically appealing









Ultra slim

No Glare

No UV/IR

Eco-friendly

Input Power	Operating Voltage	Operating Frequency	PF	Size (LxW) mm	Depth (mm)	Lumen Frequency	Lumen	ССТ
36W	100-300 V	50Hz	>0.9	595×595	32	110 lm/W	3960 lm	3000- 6500K

	CRI	Colour	Beam	Surge	THD	Operating	Mounting	
	Temperature	Angle	Sarge	1110	Temperature	Туре		
	80	6500 K	120°	Withstand 4kV	10%	-10°C to	Recess	

**APPLICATION** 



Hotels



Residential





Malls

<sup>\*</sup> Lumen may vary as per colour.





# **LED STRIP LIGHT - LUCENT Plus**

### 32 W



# COLOURS AVAILABLE

6500K		400	OK	3	3000K		
RED	C	BREEN	BLUE		PINK		

- Easy installation, Safe, Convenient & Maintenance free.
- Eco Friendly mercury free and no UV/IR.
- Easy to make patterns & designs
- Long life 50,000 hrs\*

Input Power	Input Voltage	LED	CRI	Lumen <sup>*</sup>
32W	220-240VAC, 50Hz	120LED/m	>80	3000

\* Lumen may vary as per colour.

### **APPLICATION**









Facade

Signage

Reception Area

Corridors

RECOMMENDED USAGE: Indoor Decorative Lighting

# LED STRIP LIGHT - LUCENT

### 24 W



#### COLOURS AVAILABLE

6500K	4000	OK	3000K
RED	GREEN	BLUE	PINK

- Easy installation, Safe, Convenient & Maintenance free.
- Eco Friendly mercury free and no UV/IR.
- Easy to make patterns & designs
- Long life 50,000 hrs\*

Input Power	Input Voltage	LED	CRI	Lumen
24W	220-240VAC, 50Hz	60LED/m	>80	2000

\* Lumen may vary as per colour.

### **APPLICATION**









Facade

Signage

Reception Area

Corridors

RECOMMENDED USAGE: Indoor Decorative Lighting



# LED ROPE LIGHT - LUCENT Plus

# LED ROPE LIGHT - LUCENT PIUS



#### COLOURS AVAILABLE

6500K		400	4000K 3			3000K	
RED	G	REEN	BLU	JE	PINK		









Light Output 10 meter 120 LED/ Rating withstands 700lm/mtr length meter harsh weather

Input Voltage	LED	Dimension	Lumen
220-240VAC	120LED/	L:10,000mm, W:12.5mm	700lm/
50Hz	Mtr	H:5.5mm	Mtr

<sup>\*</sup> Lumen may vary as per colour.

### **APPLICATION**









Facade

Signage

Reception Area

Corridors

RECOMMENDED USAGE : Indoor Decorative Lighting

# LED ROPE LIGHT - LUCENT



#### COLOURS AVAILABLE

6500K		400	OK	3	000K
RED	Œ	BREEN	BLU	JE	PINK









Light Output 400lm/mtr

45 meter length

60 LED/ meter

Rating withstands harsh weather

Input Voltage	LED	Dimension	Lumen
220-240VAC	60LED/	L:45,000mm, W:8mm	400lm/
50Hz	Mtr	H:6mm	Mtr

<sup>\*</sup> Lumen may vary as per colour.









Facade

Balcony

**Festive Decoration** 

Corridors







# LED ECONOMY HIGH WATTAGE - AVIDITE

# 30W | 40W | 50W











Hotels

Industry

Offices

Malls

- High brightness
- IC based driver
- Wide operating voltage
- High surge protection
- Instant start

- High lumen efficacy
- Eco-friendly
- THD<20%
- No glare
- Non dimmable

Input Power	Size(mm) ØxH	Beam Angle	PF	Lumen	ССТ
30W	100×151	180°	0.9	3000	3000-6500K
40W	117×167	180°	0.9	4000	3000-6500K
50W	139x189	180°	0.9	5000	3000-6500K

<sup>\*</sup> Lumen may vary as per colour.



# LED STREET LIGHT WITH LENS - SUPREMUS

# 20W | 25W | 30W | 40W | 60W | 90W | 100W











High Brightness

Non Dimmable

Ecofriendly

No Glare

Input Power	ССТ	CRI	Beam Angle	Lumen	IP
20W	6500K	80	120°	2000	IP 66
25W	6500K	80	120°	2500	IP 66
30W	6500K	80	120°	3000	IP 66
40W	6500K	80	120°	4000	IP 66
50W	6500K	80	120°	5000	IP 66
80W	6500K	80	120°	8000	IP 66
100W	6500K	80	120°	10000	IP 66

\* Lumen may vary as per colour.

### **APPLICATION**





Warehouses





Railway

Industry

Terminals





## 30W | 50W | 80W | 100W



- High lumen efficacy.
- Protection against open circuit voltage, short circuit, over voltage, reverse polarity, under voltage over temperature.
- Pressure die cast aluminium alloy housing for effective thermal management.





120° Beam Angle

Long Life 50,000 hrs

Input Power	Input Voltage	Lumen(Im)* @CDL	CRI	PF	IP
30W	220-240VAC, 50Hz	3000	>80	>0.95	IP66
50W	220-240VAC, 50Hz	5000	>80	>0.95	IP66
80W	220-240VAC, 50Hz	8000	>80	>0.95	IP66
100W	220-240VAC, 50Hz	10000	>80	>0.95	IP66









Garden lighting

Factory lighting

Warehouses

Industry



### **TECHNICAL FEATURES**

#### Luminous flux:

The luminous flux describes the quantity of light emitted by a light source. The luminous efficiency is the ratio of the luminous flux to the electrical power consumed (lm/W). It is a measure of a light source's economic efficiency. Unit: Lumen (lm)

#### Luminous intensity:

The luminous intensity describes the quantity of light that is radiated in a particular direction. This is a useful measurement for directive lighting elements such as reflectors. It is represented by the luminous intensity Distribution curve (LDC). Unit: Candela (cd)

#### Illuminance:

Illuminance describes the quantity of luminous flux falling on a surface. Relevant standards specify the required illuminance (e.g. EN 12464 "Lighting of indoor workplaces"). Unit: LUX (Ix)

#### Luminance:

Luminance is the only basic lighting parameter that is perceived by the eye. It describes on the one hand a light source's impression of brightness, and on the other, a surface and therefore depends to a large extent on the degree of reflection (color and surface). It is expressed as candelas per square meter (Metric units). Unit: cd/m2

#### Color Rendering Index (CRI):

A scale of the effect of a light source on the color appearance of an object compared to its color appearance under a reference light source. A low CRI rating suggests that the colors of objects will appear unnatural under that particular light source.

Color Rendering Index (Ra)	Real Object Color Appreance
Ra < 60	Poor
60 < Ra < 80	Good
80 < Ra < 90	Very Good
90 < Ra < 100	Excellent

#### Correlated Color Temperature (CCT):

The color temperature is a specification of the color appearance of a light source, relating the color to a reference source heated to a particular temperature, measured by the thermal unit Kelvin (K).

Color	Color Temperature	Appearance	Association
WW (Warm White)	Upto 3300 K	Raddish	Warm
NW (Neutral White)	3300- 5300 K	White	Neutral
CDL (Cool Day Light)	From 5300 K	Bluish	Cool

Luminaries: A device used to distribute or modify light produced by light sources installed within it.

LED: Abbreviation for light emitting diode. A developing illumination technology which consumes lower energy than similar light sources.

Light: Light is that part of the electromagnetic spectrum that is perceived by our eyes. The wavelength range is between 380 and 780 nm. The cones come on during the day and we see colors, whereas at night the rods take over and we only see shades of grev.

Light source: An electrical device used to produce light, such as ahalogen lamp, a neon tube or an LED.

Beam Angle: The angle of the given photometric body, measured at the half of the maximum light intensity emitted in the main direction of the lightbeam. The angle determines the width of the light cone. Unit: Degree

Lens: Transparent or translucent medium that alters the directional characteristics of light passing through it. Used to shape the light source made of glass, poly carbonate or acrylic.

Reflector: A surface of mirrored glass, painted metal, polished metalor metalized plastic that is shaped to project the beam from a light source in a particular direction. Reflectors may be an integral part of a lamp or they may be part of the Luminaries.




# **TECHNICAL FEATURES**

Parameters	Value
Make	RR
Operating Voltage	160-270V
PF	>0.9/230V ac
THD	<20%, <15%
Luminaire Efficacy	>100lm/W @ 3000K
Color temperature	2700-6500K
CRI	>85
LED Beam Angle	60Deg, 90 Deg, 120 Deg
Frequency	50Hz
Efficiency	>90%/ 230Vac @ full Load
Driver Make	RR/ Phillips/Fullarm/Osram
LED Make	Cree/ Citizens / Nischi / Bridgelux
Surge protection	Indoor 4KV, outdoor 6KV
Burnings life	50000hrs

SMD Surface Mounted Devices

COB Chip On Board

### **Mounting Description**



#### **IP INDEX**

The Ingress Protection (IP) code denotes the protectionagainst duct, solid objects and moisture provided by the luminaire enclosure. The IP number is defined by a numerical field of two digits placed on the right of the letters IP. The first digit corresponds to the degree of protectionagainst the penetration of duct and solid matter, while the second digitcorresponds to the degree of protection against the penetration of liquids.

First digit: degree of protection against solid objects and duct

- O. Non protected
- 1. Protection against solid objects, diameter larger than
- . Protection against solid objects, diameter larger than
- 3. Protection against solid objects, diameter larger than 2.5 mm
- 4. Protection against solid objects, diameter larger than
- 1mm

50 mm

12 mm

- 5. Duct accumulation protected
- 6. Duct penetration protected

Second digit: degree of protection against moisture and water

- D. Non protected
- 1. Drip-proof against vertical water drops
- 2. Drip-proof when tilted at angles up to 150
- 3. Protection again sprinkled water when falling at angles up to 600
- 4. Splash-proof
- 5. Jet-proof
- 6. Jet-proof, powerful water jet
- 7. Water immersion for 30 minutes at a depth of 1 meter
- 8. Water submersion



that help life better. Choose from a wide range of Water Heaters, Room Heaters & Irons, each guaranteed for quality performance, tested by time.

Backed by efficient and earnest customer service, we constantly strive towards coming up with products that help make life comfortable.

Comfort manifests in not just the big things, but in the small, everyday essentials







# STORAGE WATER HEATER - ARDOR QUBE

# 15 Ltr | 25 Ltr





Highrise Building



Thermal Cutout



Magnesium

Anode Rod

Multi Functional Safety Valve



Vitreous Enameled Glass Line Tank For Long Life



High-grade Thermostat



- 5 star bee rating for low power consumption
- Adjustable temperature knob for convenience
- Suitable for pressure pumps and high rise buildings
- Puff insulation for efficient power consumption
- · Auto cut off provided for safety
- · Vitreous enameled glass line tank for long life
- Incloy heating element

Voltage	Туре	Frequency	Wattage	Rated Pressure
230V	Storage	50Hz	2 KW	8 Bar

Capacity	Dimensions (mm)				
in Litres	L	W	Н		
15	400	380	350		
25	470	400	510		













# STORAGE WATER HEATER - ARDOR QUBE

# 10 Ltr







Highrise Building



Magnesium Anode Rod



Vitreous Enameled Glass Line Tank For Long Life



Thermal Cutout



Multi Functional Safety Valve



High-grade Thermostat

- 5 star bee rating for low power consumption
- Adjustable temperature knob for convenience
- Suitable for pressure pumps and high rise buildings
- Puff insulation for efficient power consumption
- · Auto cut off provided for safety
- · Vitreous enameled glass line tank for long life

Voltage	Туре	Frequency	Wattage	Rated Pressure
230V	Storage	50Hz	2 KW	8 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
10	380	360	330













# STORAGE WATER HEATER - SUPREMUS PRO

# 10 Ltr | 15 Ltr | 25 Ltr





Highrise Building



Thermal Cutout



Magnesium Anode Rod



Nano Polymer Coated Tank



Multi Functional Safety Valve



High-grade Thermostat



- 4 star bee rating for low power consumption
- Adjustable temperature knob for convenience
- Suitable for pressure pumps and high rise buildings
- Puf insulation for efficient power consumption
- · Auto cut off provided for safety
- · Nano polymer coated tank for long life

Voltage	Type	Frequency	Wattage	Rated Pressure
230V	Storage	50Hz	2 KW	8 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
10	290	305	500
15	330	340	510
25	385	395	580













# STORAGE WATER HEATER - ARDENT PRO

# 10 Ltr | 15 Ltr | 25 Ltr







Highrise Building



Thermal Cutout



Magnesium Anode Rod



Nano Polymer Coated Tank



Multi Functional Safety Valve




High-grade Thermostat



- 4 star bee rating for low power consumption
- Suitable for pressure pumps and high rise buildings
- Puf insulation for efficient power consumption
- Auto cut off provided for safety
- Nano polymer coated tank for long life

Voltage	Туре	Frequency	Wattage	Rated Pressure
230V	Storage	50Hz	2 KW	8 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
10	315	335	450
15	320	335	505
25	370	390	555





PRODUCT	2 YEAR
HEATING ELEMENT	2 YEAR
ON TANK	5 YEAR





# STORAGE WATER HEATER - SUPREMUS+

# 15 Ltr | 25 Ltr





Digital Temperature Display



Durable, Rust Proof ABS Body



Magnesium Anode Rod



Highrise Building



Thermal Cutout



Multi Functional Safety Valve

# • 4 star bee rating - for low power consumption

- Adjustable temperature knob for convenience
- Suitable for pressure pumps and high rise buildings
- Puf insulation for efficient power consumption
- · Auto cut off provided for safety
- · Vitreous enameled glass line tank for long life

Voltage	Туре	Frequency	Wattage	Rated Pressure
220V	Storage	50Hz	2 KW	8 Bar

ſ	Capacity	Dimensions (mm)		
	in Litres	L	W	Н
	15	330	340	490
	25	385	395	550













# STORAGE WATER HEATER - SUPREMUS GLS

# 06 Ltr | 10 Ltr | 15 Ltr | 25 Ltr | 35 Ltr | 50 Ltr







High-grade Thermostat



Rust Proof Body



Magnesium Anode Rod



Multi Functional Safety Valve



Vitreous Enameled Glass Line Tank For Long Life

- Suitable for high rise buildings and high pressure pumps
- Safety feature- Multi functional valve, Thermostat, Thermal cutout
- Adjustable temperature control knob

Note: For 35 & 50 Litres the star rating is 2

Voltage	Туре	Frequency	Wattage	Rated Pressure
220V	Storage	50Hz	2 KW	8 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
6	325	340	415
10	325	340	475
15	365	380	570
25	400	425	610
35	430	450	650
50	430	450	750





PRODUCT	2 YEAR
HEATING ELEMENT	2 YEAR
ONTANK	7 YEAR







# STORAGE WATER HEATER - CALESCENT

# 10 Ltr | 15 Ltr | 25 Ltr





High-grade Thermostat



Magnesium Anode Rod



Multi Functional Safety Valve



Glass Line Tank For Long Life



Metal Body




- Suitable for high rise buildings and high pressure pumps
- · Safety feature- Multi functional valve, Thermostat, Thermal cutout
- · Adjustable temperature control knob

Voltage	Туре	Frequency	Wattage	Rated Pressure
220V	Storage	50Hz	2 KW	8 Bar

Capacity in Litres	Dimensions (mm)		
	L	W	Н
10	315	335	450
15	320	335	505
25	370	390	555













#### STORAGE WATER HEATER - ARDENT

#### 10 Ltr | 15 Ltr | 25 Ltr

**VERTICAL MOUNTING** 





High-grade Thermostat



Metal Body



Thermal Cutout



Fusible Plug



Puff Insulation







- Safety feature -Thermostat & Thermal Cutout, Pressure release valve & fusible plug
- High grade & high gauge stainless steel tank SS 304 L
- Anti vacuum system
- · Powder coated metal body for long life

Voltage	Туре	Frequency	Wattage	Rated Pressure
220V	Storage	50Hz	2 KW	6.5 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
10	275	265	490
15	350	295	475
25	410	390	540





PRODUCT	2 YEAR
HEATING ELEMENT	2 YEAR
ON TANK	5 YEAR





# WATER HEATER

Disclaimer: Due to continuous product improvements, Product Image shown may vary from actual product.

#### INSTANT WATER HEATER - RAVISH

#### 03 Ltr







Fire retardant power cord

thermostat







304 tank



proof outer body

**Dual LED** Indicator

Anti Siphon protection

- Fire retardant power cord for maximum safety
- Weldless SS 304 L tank that enhances resistance to corrosion ensuring long tank life
- Rust and shock proof outer body
- · Capillary thermostat for higher efficiency
- · Leakage proof integrated pressure valve
- · Anti Siphon protection designed to prevent any backflow of water and protect the heating element from dry heating
- Disc type thermal cut-out for higher efficiency

Voltage	Туре	Frequency	Wattage	Rated Pressure
230V	Instant	50Hz	3 KW	6.5 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
03	380	220	195



PRODUCT	2 YEAR
HEATING ELEMENT	2 YEAR
ON TANK	5 YEAR







#### **INSTANT WATER HEATER - CALID Plus**

03 Ltr







High-quality Thermostat



Thermal Cutout



Stainless Steel Tank



Release Value




Indicator

- Thermostat, Thermal Cut Out & Pressure Release Valve (PRV) for Safety Purpose
- High Grade & High Gauge Stainless Steel Tank SS 304 L
- Rust Proof Body

Voltage	Туре	Frequency	Wattage	Rated Pressure
230V	Instant	50Hz	3 KW	6.5 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
03	202	196	365





PRODUCT	2 YEAR
HEATING ELEMENT	2 YEAR
ON TANK	5 YEAR



#### **INSTANT WATER HEATER - CALID Pro**

#### 05 Ltr







High-quality Thermostat





Thermal Cutout



Indicator



Suitable for Low & mid res Buildings



• 3 level Safety Feature - Thermostat and Thermal Cutout and Pressure Release Valve(PRV) for Safety Purpose


- Thick High Grade Stainless Steel (SS 304L) Weldless Tank
- Rust & Shock-Proof Plastic body
- LED Indicator for Power and Heating

Voltage	Type	Frequency	Wattage	Rated Pressure
230V	Instant	50Hz	3 KW	6.5 Bar

Capacity	Dimensions (mm)		
in Litres	L	W	Н
05	255	225	435



ARRAWID	PRODUCT	2 YEAR
RRANTY	HEATING ELEMENT	2 YEAR
WARRAN	ON TANK	5 YEAR





#### **GAS WATER HEATER - LPG/PNG**

#### 06 Ltr











3-Row Burner withdouble ignition



Summer / Winter

Mode

Adjustable temperature

control

- Better safety during gas flow with single solenoid valve
- Secondary automatic overheat protection Thermal cutout
- · Flame failure device
- Gas leakage protection
- Mesh on water inlet, gas inlet and chimney to avoid scaling, blockage, dry heating and impurities
- Variable pressure Compatibility Suitable for low and high water pressure (upto 8 bar)
- · Safety lock To control the ON/OFF operation
- · ISI Certified product For safety and quality

	Rated Capacity	Rated Heat Input	Frequency	Rated Pressure
	6 L/min	10kW	50Hz	LPG- 2900 Pa / PNG-2000 Pa

Capacity	Dimensions (mm)			
	in Litres	L	W	Н
	06	290	140	490



# IMMERSION WATER HEATER

Disclaimer: Due to continuous product improvements, Product Image shown may vary from actual product.

#### **IMMERSION WATER HEATER**

#### 1.0 KW | 1.5 KW





- Shock proof handle complete protection against electric shock
- Water Proof Handle
- · Instant heating
- · Water level indicator

Voltage	230V
Туре	Immersion Heater
Frequency	50Hz
Wattage	1.0 KW / 1.5 KW



- · Shock proof bakelite handle
- Power Indicator
- · Instant Heating
- · Water Level Indicator
- · Energy efficient

Voltage	230V	
Туре	Immersion Heater	
Frequency	50Hz	
Wattage	1.0 KW / 1.5 KW	



Heavy copper heating element



Nickel Plating for Corrosion Resistance



Plastic Shockproof waterproof handle



Neon Indicator\*



Sturdy Bucket Clip





#### **HEAT CONVECTOR - RH 1**

#### 2000 W

#### **HEAT CONVECTOR - RH 2** 2000 W









- · Twin Turbo Design.
- · Two Heating Positions.
- · Thermal cutout.
- · Instant heating.
- · Indicator Light.
- · Portable.

Voltage	230V
Frequency	50Hz
Wattage	2000 W
Thermal cut-out	Provided
Heating position	1000W /
	2000W



Two Heating **Positions** 



Thermal Cutout



Indicator Light



Twin Turbo Motor

•	Twin	Turbo	Design.
	1 44111	1 41 50	Design.

- Two Heating Positions.
- Thermostat & Thermal cutout.
- · Instant heating.
- · Indicator Light.
- · Portable.

	)

Two Heating **Positions** 



Twin Turbo High-grade Motor



Voltage

Frequency

Thermal cut-out

Heating position

Wattage

Thermostat & Thermal Cutout



230V

50Hz

2000 W

Provided

1000W /

Adjustable Heights

#### QUARTZ ROOM HEATER

### RR

230V

50Hz

400 W /

800 W

400 / 800W









Voltage	230V
Frequency	50Hz
Wattage	400 W /
	800 W

- Twin Quartz tube for direct heating.
- Safety tip over switch cuts off the heater, in case it tilts or falls.
- Two heat settings-400 watt/800 watt, for maintaining desired room temperature.



Indicator Light

Switch for heat setting 400w/800w



Quartz Heating Tubes



2 HEATING POSITION



ELEGANT DESIGN



Safety Tip Over Switch







Voltage

Frequency

Wattage

- Twin Quartz tube for direct heating.
- Safety tip over switch cuts of the power supply, in case it tilts or falls.
- Two heat settings-400 watt/800 watt, for maintaining desired room temperature.
- Powder coated finish to prevent corrosion.

#### CALID HALOGEN HEATER

# RRAPPLIANCES



- Oscillation upto 180° at all heat setting
- Elegant Panel design that matches your Home Décor
- Ideal for use in small room for Instant Heating
- Easy to switch between heat settings and manage oscillation function
- Safety tip over switch that cuts OFF the Heater incase it Tilts or Falls

Voltage	230V	
Frequency	50Hz	
Wattage	1200 W	
Heating	400W	
Position	800 W	
	1200 W	



Easy Lift Handle



180° auto OSCILLATION



3 Heating rod



Safety Tip Over Switch







1000 W

#### **ARDENT Plus** 1000 W











- Weilburger Non Stick Coated Sole Plate for Instant Heating
- Uniform Heat Distribution across the sole plate
- PBT Body with stain resistant, High Strength, tough and stiff characteristics
- Ergonomic stylish handle



Easy Handle Grip



360° Swivel Cord



Variable Temperature Control







- Weilburger non stick coated sole plate for instant heating
- Uniform heat distribution across the sole plate
- Ergonomic stylish handle
- Customize settings for different fabrics



Easy Handle Grip



Indicator Light



Variable Temperature Control

#### **ESTELLA Plus**

#### 1000 W







- Weilburger Non Stick Coated Sole Plate for Instant Heating
- Uniform Heat Distribution across the sole plate
- Ergonomic Stylish Design
- Reliable Snap Action Thermostat



Indicator Light



Thermal Fuse



Adjustable Temperature Control



360° Swivel Cord

#### SILK FLOW Plus









- Uniform heating
- · Non stick coating
- · Ergonomic handle design
- Multiple temperature levels
- Reliable snap-action thermostat



Indicator Light



360° Swivel Cord



Variable Temperature Control









- Saves time, while ironing out wrinkles on clothes
- Aluminium alloy sole plate with to Weilburger Non Stick Gold Coating
- Safety thermal fuse helps avoid Accidental burns by preventing over-heating.
- ISI safety hallmark by BIS



Indicator Light



Weilburger Non Stick Gold Coated Sole Plate



Thermal Fuse



Adjustable Temperature Control



#### SKYWIND DESERT ROOM AIR COOLER

#### 90 Ltr | 70 Ltr







High Air throw



Inverter compatible



Thermal overload Protection for motor and Pump



Completely Collapsible Louvers



Honeycomb pad



Multi Directional Castor Wheels

Tank Capacity	90 Ltrs	70 Ltrs
Voltage	230v/50hz	230v/50hz
Wattage (W)	200	200
Air Throw (ft)	60	60
Air Delivery (m³/hr)	4600	4600
Speed (RPM)	1350	1350
Cooling Area(Ft²)	500	500
Body Material	PP	PP
Product Dimensions in mm (LxBxH)	605x480x1060	605x480x1040



Warranty

#### CALIDFLOE DESERT ROOM AIR COOLER

#### 70 Ltr | 55 Ltr







High Air throw



Inverter compatible



Thermal overload Protection for motor and Pump



Ice Chamber



Honeycomb/ Woodwool pad



Multi Directional Castor Wheels

Tank Capacity	70 Ltrs	55 Ltrs
Voltage	230v/50hz	230v/50hz
Wattage (W)	200	200
Air Throw (ft)	50	50
Air Delivery (m³/hr)	4500	4500
Speed (RPM)	1350	1350
Cooling Area(Ft²)	400	400
Body Material	PP	PP
Product Dimensions in mm (LxBxH)	590x340x1190	590x340x1150



Note: Available in Honeycomb and Woodwool pad

#### **ESTELLA TOWER ROOM AIR COOLER**

#### 35 Ltr







High Air Delivery



Inverter compatible



Thermal overload Protection for motor and Pump



Completely Collapsible Louvers



Honeycomb pad



Multi Directional Castor Wheels

Tank Capacity	35 Ltrs
Voltage	230v/50hz
Wattage (W)	150
Air Throw (ft)	35
Air Delivery (m³/hr)	1350
Speed (RPM)	1400
Cooling Area(Ft²)	150
Body Material	ABS
Product Dimensions in mm (LxBxH)	355x350x1150



#### ESTELLA PERSONAL ROOM AIR COOLER

#### 25 Ltr







High Air Delivery



Inverter compatible



Thermal overload
Protection for
motor and Pump



Completely Collapsible Louvers



Honeycomb pad



Multi Directional Castor Wheels

Tank Capacity	25 Ltrs
Voltage	230v/50hz
Wattage (W)	150
Air Throw (ft)	35
Air Delivery (m³/hr)	1350
Speed (RPM)	1350
Cooling Area(Ft²)	150
Body Material	PP
Product Dimensions in mm (LxBxH)	460x330x740



Product Warranty

#### CALIDFLOE WINDOW ROOM AIR COOLER

## RRAPPLIANCES

50 Ltr





Water Level Indicator



Inverter compatible



Thermal overload Protection for motor



Swing



Woodwool pad



High Air Delivery

Tank Capacity	50 Ltrs
Voltage	230v/50hz
Wattage (W)	220
Air Throw (ft)	40
Air Delivery (m³/hr )	2000
Speed (RPM)	1280
Cooling Area(Ft²)	250
Body Material	PP
Product Dimensions in mm (LxBxH)	660x560x550



Note: Trolly sold separately



#### **RR Kabel Limited**

#### Corp. Office:

Alembic Business Park (West), Ground Floor, Bhailal Amin Marg, Gorwa, Vadodara - 390 003, Gujarat

#### Regd. Office:

Ram Ratna House, Oasis Complex, P. B. Marg, Worli, Mumbai, 400 013, Maharastra

Tel No.: +91-22-24929009 / 24924144

#### Customer Care Toll Free No.: 18001032676

Email: customercare@rrglobal.com

Terms & conditions apply.

The products may differ as per catalog due to continuous improvements.

The colour shade of the products shown may differ from the actual products colour due to printing limitations